



DOM & JQUERY

GETTING/SETTING CONTENT

<code>element.innerHTML = 'Hello';</code>	<i>text content</i>
<code>element.src = 'images/fun.png';</code>	<i>src attribute value</i>
<code>element.className = 'success';</code>	<i>class attribute value</i>
<code>element.value = '';</code>	<i>input box value</i>

ADDING CONTENT TO THE DOM

<code>document.createElement('li');</code>	<i>create a new element of the specified type</i>
<code>document.createTextNode('Today's Weather');</code>	<i>create a node containing specified text</i>
<code>parent.appendChild(child);</code>	<i>append child node to parent node</i>

EVENT LISTENERS

element reference method to add event listener type of event

```
button.addEventListener('click', function() {  
    // your code here  
}, false);
```

final boolean parameter
for backward compatibility

function to run
when event is triggered

VANILLA JS VS JQUERY SYNTAX

Vanilla JS

<code>document.querySelector('.intro')</code>
<code>document.querySelectorAll('.intro')</code>
<code>document.createElement('h1')</code>
<code>document.createTextNode('banana')</code>
<code>list.appendChild(item1)</code>

jQuery

<code>\$('.intro')</code>	<i>select element by selector</i>
<code>\$('.intro')</code>	<i>select elements by selector</i>
<code>\$(<h1>')</code>	<i>create an element</i>
<code>item1.('banana')</code>	<i>create a text node</i>
<code>list.append(item1)</code>	<i>append</i>

JQUERY

METHODS

```
$('#heading').text('Your Name');  
$('.main').find('h1').addClass('warning');
```

EVENTS

```
$(li).on('click', function() {  
    // do something  
});
```

SELECTORS

\$('.className')	<i>class selector</i>
\$('#idName')	<i>id selector</i>
(\$h1, h2, h3')	<i>multiple selectors</i>
(\$li a')	<i>descendent selector</i>

(\$h1 > a')	<i>direct child selector</i>
(\$h1 + a')	<i>adjacent sibling selector</i>
(\$h1 ~ a')	<i>general sibling selector</i>

FINDING ELEMENTS

(\$p).find('a');	<i>find descendants</i>
(\$p).children('a');	<i>find children</i>

(\$p).parent('div');	<i>find parent</i>
(\$p).siblings('a');	<i>find siblings</i>

GETTING/SETTING CONTENT

```
($p).text('Hello');  
($img).attr('src', 'images/fun.png');
```

```
($p).addClass('success');  
($p).removeClass('error');  
($p).toggleClass('highlight');
```

EFFECTS/ANIMATION

```
($p).show();  
($p).hide();  
($div).fadeIn('slow');  
($h2 a').fadeOut('fast')
```

```
($p).slideUp(350);  
($p).slideDown(600);  
($h1).slideToggle(300);
```